

Aluminium Twol Bolt Cable Cleat

Type ATC

Material : Aluminium Alloy
Finish : Natural Epoxy Coated

Suitable for use with LV/MV & HV Cables.
Few range accommodates wide range of cable dia.

Type Tested as per IEC 61914



PART NO	CABLE DIA A (MM) MIN.	CABLE DIA A (MM) MAX.	B	C	D	E	F	G	H
ATC 30-40	30	40	40.20	21	4	23.60	75.50	95	45
ATC 40-50	40	50	50.20	20.20	4	30	84.50	110	45
ATC 51-57	51	57	57.10	32.00	6.50	33.50	84.30	114.50	49
ATC 57-64	57	64	64.40	28.80	4	37.80	94	122	48
ATC 64-70	64	70	70.50	32.20	4	40	98	124	46
ATC 70-76	70	76	76.50	35.20	4	44.80	110.70	136	48
ATC 76-83	76	83	83.50	36.20	6	48	117.70	143	52
ATC 83-89	83	89	89.50	41	5	48.80	124.20	149.20	60
ATC 89-95	89	95	95.50	44.80	5	52.80	130.50	158.20	59
ATC 95-101	95	101	101.50	47.80	5	55.3	126.10	154	65
ATC 101-108	101	108	108	57	6	69	136.50	165	65
ATC 108-115	108	115	114.10	60	6	62	142	171	65
ATC 115-125	115	125	125.50	56	6	63.50	150	175	85
ATC 125-135	125	135	136.10	62.80	6	70.20	166	194	85

